

## DECLARATION OF PERFORMANCE (acc. EU 305/2011, Annex V)

No. DOP 009-001-23

1. Unique identification code of the product-type:

**UdiRECO WF-EN 13171 - AFr5 - T3 - MU2 -TR1 // WF-EN 13171 - T5 - WS1,0 - MU5 - CS(10/Y)150 - DS(70,90)3 - TR20**

2. Type, batch, or serial number or any other element allowing identification of the construction product as required under Article 11 (4) of the CPR:

**see product label**

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

**Thermal insulation for the buildings**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

**UdiDÄMMSYSTEME GmbH, Oberfrohaer Straße 2, 09117 Chemnitz, Germany  
eMail:info@udidaemmsysteme.de**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

**not relevant**

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V

**System 3**

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

**Notified certification body performed the determination of the product type on basis of type testing and type calculation**

8. If the construction project is directed by an European technical evaluation:

**not relevant**

9. Declared performances

Essential characteristics		Performance Ausgleichs- ebene	Performance Putzträger	Harmonised technical specification
Reaction on fire	4.2.6 reaction on fire	Klasse E	Klasse E	EN 13171:2012 + A1:2015
Release of dangerous substances to the indoor environment	4.3.15 release of dangerous substances	NPD (No Performance Determined)	NPD (No Performance Determined)	
Acoustic absorption index	4.3.12 Sound absorption	NPD	NPD	
Impact noise transmission index ( for floors)	4.3.10 Dynamic stiffness	NPD	NPD	
	4.3.11.1 Thickness $d_L$	NPD	NPD	
	4.3.11.3 Compressibility	NPD	NPD	
	4.3.13 Air flow resistivity	Af <sub>r</sub> 5	NPD	
Direct airbourne sound insulation index	4.3.13 Air flow resistivity	Af <sub>r</sub> 5	NPD	
Continuous glowing combustion	4.3.17 Continuous glowing combustion	NPD	NPD	

### FIRMENSITZ

UdiDÄMMSYSTEME GmbH  
Oberfrohaer Straße 2  
D-09117 Chemnitz

Telefon +49 (0)371 33 71 38 0  
Telefax +49 (0)371 33 71 38 64  
E-Mail info@udidaemmsysteme.de

### LOGISTIK / ABHOLLAGER

UdiDÄMMSYSTEME GmbH  
Röhrsdorfer Allee 41  
D-09247 Chemnitz OT Röhrsdorf

Telefon +49 (0)371 33 71 38 0  
Telefax +49 (0)371 33 71 38 64  
E-Mail info@udidaemmsysteme.de

### GESCHÄFTSFÜHRUNG

Anka Unger

HRB 30875  
Ust.-ID.-Nr.: DE 310 743 696  
Steuer-Nr.: 215/121/07696  
Gerichtsstand ist Chemnitz

### BANKVERBINDUNGEN

Sparkasse Chemnitz  
IBAN DE47 8705 0000 0710 0543 19  
BIC/SWIFT CHEKDE81XXX

Commerzbank  
IBAN DE61 8704 0000 0113 6050 00  
BIC/SWIFT COBADEFFXXX

Essential characteristics		Performance Ausgleichs- ebene		Performance Putzträger		Harmonised technical specification
Thermal resistance	4.2.1 Thermal resistance and thermal conductivity	$\lambda_D$	0,038 W/mK	$\lambda_D$	0,048 W/mK	EN 13171:2012 + A1:2015
	4.2.1 Diathermancy resistance	$R_D$	= 1,05 - 4,20 m²K/W	$R_D$	= 0,80 m²K/W	
	4.2.3 Thickness	siehe Produkteinleger				
	4.2.3 Thickness class	T3		T5		
Water permeability	4.3.8 short term water absorption	NPD		WS1,0		
Water vapour permeability	4.3.9 Water vapour transmission	MU2		MU5		
Compressive strenght	4.3.3 Compressive stress or compressive strenght	NPD		CS(10/Y)150		
	4.3.6 Point load	NPD		NPD		
Durability of reation on fire against heat, weathering, ageing / degradation	4.2.7 durability characteristics	NPD		NPD		
Durability of thermal resistance against heat, weathering, ageing / degradation	4.2.1 Thermal resistance and thermal conductivity	$\lambda_D$	0,038 W/mK	$\lambda_D$	0,048 W/mK	
		$R_D$	= 1,05 - 4,20 m²K/W	$R_D$	= 0,80 m²K/W	
	4.3.2 Durability characteristics	NPD		NPD		
	4.3.2.2 Dimensional stability	NPD		NPD		
	4.3.2.2 Dimensional stability under specific temperature	NPD		DS(70,90)3		
Tensile / Flexural strength	4.2.7 Dimensional stability under specific temperature and moisture	NPD		NPD		
	4.3.5 Tensile strength perpendicular to faces	NPD		NPD		
	4.3.4 Tensile strength parallel to faces	TR1		TR20		
	Durability of compressive strength against ageing / degradation	4.3.7 Compressive creep	NPD		NPD	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



ppa. Robby Fitzner  
Authorized officer // Head of application technology

Chemnitz, 09.06.2023  
.....  
place and date of issue

#### FIRMENSITZ

UdiDÄMMSYSTEME GmbH  
Oberfrohaer Straße 2  
D-09117 Chemnitz

Telefon +49 (0)371 33 71 38 0  
Telefax +49 (0)371 33 71 38 64  
E-Mail info@udidaemmsysteme.de

#### LOGISTIK / ABHOLLAGER

UdiDÄMMSYSTEME GmbH  
Röhrsdorfer Allee 41  
D-09247 Chemnitz OT Röhrsdorf

Telefon +49 (0)371 33 71 38 0  
Telefax +49 (0)371 33 71 38 64  
E-Mail info@udidaemmsysteme.de

#### GESCHÄFTSFÜHRUNG

Anka Unger

HRB 30875  
Ust.-ID.-Nr.: DE 310 743 696  
Steuer-Nr.: 215/121/07696  
Gerichtsstand ist Chemnitz

#### BANKVERBINDUNGEN

Sparkasse Chemnitz  
IBAN DE47 8705 0000 0710 0543 19  
BIC/SWIFT CHEKDE81XXX

Commerzbank  
IBAN DE61 8704 0000 0113 6050 00  
BIC/SWIFT COBADEFFXXX